



NetVanta 3305

Multi-slot Access Router Supporting up to Three T1s of Bandwidth

Product Features

- Dual interchangeable Network Interface Modules (NIMs)
- Dual auto-sensing 10/100Base-T interfaces for LAN segmentation
- Stateful inspection firewall for network security
- Quality of Service (QoS) for delay-sensitive traffic like Voice over IP (VoIP)
- Inherent URL filtering
- Optional DSX-1 interface supplies TDM voice transport
- Comprehensive PPP dial backup scheme prevents network downtime
- VLAN Trunking (802.1Q) for routing between VLANs
- Recognizable Command Line Interface (CLI) and intuitive Web-based Graphical User Interface (GUI)
- Network Address Translation (NAT) for IP Address Concealing
- Optional VPN for secure corporate connectivity across the Internet
- Industry-leading five-year North American warranty

The NetVanta® 3000 Series of modular access routers is designed for cost-effective Internet access, corporate Frame Relay, point-to-point connectivity, ADSL, and Virtual Private Networking (VPN). The NetVanta 3000 Series currently consists of the NetVanta 3200, 3205, and 3305 with a variety of interchangeable NIMs and Dial Backup Modules (DIMs).

Modular Hardware

The NetVanta 3305 is a dual-slot, dual-Ethernet 1U high, rackmountable metal enclosure. A single slot within any of the NetVanta 3000 Series will house a variety of NIMs and DIMs. For dial backup, an analog modem DIM or an ISDN BRI DIM is available for preventing downtime by dialing around a failed circuit to any PPP-compliant device.

Standards Protocols

The versatile hardware platform of the NetVanta 3305 is further complemented with the ADTRAN® Operating System (AOS). The AOS allows for the support of static and default routes, demand and policy-based routing, and allows for fast, accurate network convergence using routing protocols such as BGP, OSPF, and RIP. In addition, the AOS terminates MPLS, Frame Relay, Multilink Frame Relay, PPP, Multilink PPP, PPPoE, PPPoA, RFC 1483, and HDLC Wide Area Network (WAN) protocols. Multihoming is also available to provide redundant or backup WAN links to multiple ISPs, guaranteeing a wide-area connection.

QoS

QoS is also supported for delay-sensitive traffic like VoIP or video. To prioritize mission-critical traffic and control network congestion, the NetVanta 3305 uses Low Latency Queuing, Weighted Fair Queuing (WFQ), Class-based WFQ, and DiffServ marking to establish priority of IP packets routed over the WAN.

VoIP Ready

In combination with the QoS features, a specialized Session Initiation Protocol (SIP) Application Layer Gateway (ALG) allows SIP traffic to traverse NAT-enabled firewalls. For an enterprise network, this interoperability allows IP PBXs, phones, and other SIP-based devices to set up, tear down, and pass voice and call control messages seamlessly through the integral NAT-enabled firewall.

Security

For added security, AOS provides a powerful, high-performance stateful inspection firewall that can identify and protect against common Denial of Service (DoS) attacks like TCP syn flooding, IP spoofing, ICMP redirect, ping-of-death, and IP reassembly problems.

In addition, the AOS is capable of providing an inherent URL-filtering package without the use of an external server. URL filtering is another level of security that allows system administrators to restrict Internet access by permitting or denying specific URLs. This URL-filtering feature also includes the ability to produce top website reports of the most frequently requested websites, allowing system administrators to modify the URL filter lists.

The NetVanta 3305 also supports up to 500 simultaneous VPN tunnels, while supporting encryption algorithms like DES, 3DES, and AES. By supporting IPSec, the NetVanta 3305 is fully compatible with other IPSec VPN-equipped NetVanta products.

Administration

The AOS offers both a CLI that mimics the widely deployed, industry *de facto* standard and an intuitive Web-based GUI with step-by-step configuration wizards.



ADTRAN, Inc.

Attn: Enterprise Networks
901 Explorer Boulevard
Huntsville, AL 35806

P.O. Box 140000
Huntsville, AL 35814-4000

256 963-8000 voice
256 963-8699 fax

General Information
800 9ADTRAN
info@adtran.com
www.adtran.com

Pre-Sales

Technical Support

800 615-1176 toll-free
application.engineer@adtran.com
www.adtran.com/support

Where to Buy

877 280-8416 toll-free
channel.sales@adtran.com
www.adtran.com/where2buy

Post-Sales

Technical Support

888 423-8726
support@adtran.com
www.adtran.com/support

ACES Installation & Maintenance Service

888 874-ACES
aces@adtran.com
www.adtran.com/support

International Inquiries

256 963 8000 voice
256 963-6300 fax
international@adtran.com
www.adtran.com/international

For the regional office nearest you, visit:

www.adtran.com/regional



ADTRAN is an ISO 9001, ISO 14001, and a TL 9000 certified supplier.

61200880L1-8N AOS 17.1 May 2008
Copyright © 2008 ADTRAN, Inc.
All rights reserved.

NetVanta® 3305



Multi-slot Access Router Supporting up to Three T1s of Bandwidth

Physical Interface

- **Dual NIM:** 56/64k, T1/FT1, T1/FT1 with DSX-1, Dual T1s, E1/FE1, E1/FE1 with G.307, ADSL, SHDSL, and Serial
- **DIM:** Analog Modem and ISDN BRI (U and S/T)
- **Dual LAN:** Auto-sensing 10/100Base-T Full Duplex (RJ-45)
- Console Port

Diagnostics LEDs

- Power
- **Dual WAN:** link, transmit, receive
- **Dual LAN:** link, transmit, receive
- **Dual Dial Backup:** transmit and receive

Processor and Memory

- 120 MHz, Motorola MPC 866
- **RAM:** 64 MB
- **FLASH:** 16 MB

Quality of Service (QoS)

- Class-based Weighted Fair Queuing, Low Latency, and Weighted Fair Queuing
- DiffServ Packet Marking and Recognition
- Frame Relay Fragmentation
- Traffic Monitoring (NetFlow 9)

Protocols

- eBGP/iBGP
- OSPF
- RIP (v1 and v2)
- PIM Sparse Mode
- Demand Routing
- Policy-based Routing
- GRE
- ATM (ADSL)
- Frame Relay
- Multilink Frame Relay
- Layer 3 Backup
- PPP
- Multilink PPP
- PPPoE
- PPPoA
- IGMP v2
- RFC 1483
- HDLC
- PPP Dial Backup
- PAP and CHAP
- Multihoming
- Multi-VRF CE

Administration

- Familiar Command Line Interface (CLI)
- Web-based GUI
- n-Command® support
- SNMP v2
- TCL Scripting
- SYSLOG logging
- Email alerts (SMTP)
- Policy statistics

Frame Relay

- Point-to-point
- RFC 1490 Encapsulation (Multiprotocol Over Frame Relay)
- **LMI types:** LMI, ANSI (Annex D), CCITT (Annex A) and Static

DHCP

- Client, Server, and Relay

Security

Firewall

- Stateful Inspection Firewall
- Denial of Service (DoS) Protection
- Access Control Lists
- Application Level Gateways (ALGs)

Network Address Translation

- Basic NAT (1:1), NAT (Many:1), and 1:1 Port Translation
- NAT-compatible SIP ALG

Secure Management

- Multi-level access control
- RADIUS AAA
- TACACS+
- SSH CLI and SSL GUI
- Port Authentication (802.1x)

Content Filtering

- Inherent URL filter
- Top website reports
- Integration with Websense®

Optional Virtual Private Network (VPN)

- **IPSec Mode:** 100 Tunnels
- **Encryption:** DES, 3DES, and AES
- **Authentication Mechanisms:**
 - XAUTH
 - X.509 Digital certificates
 - Preshared keys
 - Secure ID
 - DSS Signatures

Environment

- **Operating Temperature:** 0° to 50 °C (32° to 122 °F)
- **Storage Temperature:** -20° to 70 °C (-4° to 158 °F)
- **Relative Humidity:** Up to 95%, non-condensing

Physical

- **Chassis:** 1U rackmountable metal enclosure
- **Dimensions:** 1.25" H, 17.25" W, 7.75" D
- **Weight:** 7.5 lbs.
- **Power:** 100-250 VAC, 50/60 Hz, 6 W max.

Agency Approvals

- FCC Part 68
- Industry Canada CS03
- UL & Canadian UL (CUL), IEC/EN, CSA
- CE Mark
- RoHS ("E" versions)

Ordering Information

Equipment	Part #
Systems	
NetVanta 3305 Chassis	1202880E1
with T1/FT1 NIM	4200882L1
with T1/FT1+DSX-1 NIM	4200883L1
NetVanta 3305 Chassis with VPN	4200880E2
VPN Upgrade	4200368E1

ADTRAN believes the information in this publication to be accurate as of publication date, and is not responsible for error. Specifications subject to change without notice. ADTRAN and NetVanta are registered trademarks of ADTRAN, Inc. and its affiliates in the U.S. and certain other countries. All other trademarks mentioned in this document are the property of their respective owners. Five-year warranty applies only to products sold in North America.

ADTRAN products may be subject to U.S. export controls and other trade restrictions. Any export, re-export, or transfer of the products contrary to law is prohibited. For more information regarding ADTRAN's export license, please visit www.adtran.com/exportlicense