

## **DATA SHEET**

# Polycom® VVX® 500, 501 Business Media Phones

## Performance business media phones that deliver best-in-class desktop productivity and unified communications for busy professionals

The Polycom® VVX® 500 Series performance business media phones unify superior voice capabilities and applications into a simple-to-use, yet high-performance unified communications (UC) solution. It is the ideal, all-in-one knowledge worker productivity tool, built to integrate seamlessly into a wide range of UC environments.

## Simplicity and ease of use

The Polycom VVX 500 Series phone is built for today's busy managers and knowledge workers who need a powerful, expandable office phone that keeps up with their multitasking and schedule-juggling. Building on the behavior common to mobile phones, the multitouch, gesture-based user interface of the Polycom VVX 500 makes navigation intuitive and easy.

## Maximize productivity

Designed for a broad range of environments from small and medium businesses to large enterprises, the Polycom VVX 500 Series performance business media phone improves productivity by complementing the workplace applications on the user's computer. Users benefit from such capabilities as viewing their Outlook calendar on the phone and receiving meeting reminders while still having access to their corporate directory—all while waiting for their PCs to boot. Users can also extend their PC desktop to include the Polycom VVX 500 Series screen, helping to enable simplified interactions and dialing using their PC's mouse and keyboard. Training and multipoint communication applications are complemented by the Polycom VVX 500 Series video playback capability for streaming content.

## Best-in-class deployment and administration

The Polycom VVX 500 Series is easy to deploy and simple to manage. Its enterprise-grade, Web-based, intuitive configuration method gives administrators the ability to easily set up and maintain a large number of phones throughout the entire enterprise. The built-in, broad interoperability capabilities allow IT departments to leverage previous IT infrastructure investments and achieve easy integration with third-party UC and productivity applications.

## Highly customizable and expandable

The Polycom VVX 500 Series provides personalized information at a glance, through built-in Web applications and even a digital photo frame. Polycom's "My Info Portal" serves up stocks, news, sports, weather and other streamed content directly to the phone screen. The Polycom VVX 500 Series is ready for future expansion modules and accessories for applications such as videoconferencing and even wireless networking.

#### Market-leading open standards interoperability

Designed for enhanced interoperability, leveraging and complementing the other existing IT investments of any enterprise, the Polycom VVX 500 Series delivers HD Voice™, a superior UC experience bundled with business applications. With the broadest call server interoperability in the industry, the Polycom VVX 500 Series business media phone is a flexible foundation for any organization's UC strategy.



## **Benefits**

- Improves knowledgeworker productivity
- Reduces training time through superior calling features in a sleek design and simple-to-use phone
- Cuts telephony administration and maintenance costs
- Leverages previous IT infrastructure investments
- Easy to deploy, administer, upgrade and maintain
- Delivers easy integration with third-party UC and productivity applications

## **Product specifications**

#### User interface features

- Gesture-based, multitouch-capable, capacitive touch-screen
- 3.5-in TFT LCD display at QVGA (320 x 240 pixel) resolution,
  4:3 aspect ratio
- Screensaver and digital picture frame mode
- · On-screen virtual keyboard
- Voicemail and videomail support<sup>1</sup>
- Dual USB ports (2.0 compliant) for media and storage applications
- WebKit-based browser
- · Adjustable base height
- Unicode UTF-8 character support. Multilingual user interface including Chinese, Danish, Dutch, English (Canada/ US/UK), French, German, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Russian, Slovenian, Spanish and Swedish

## Audio features

- Polycom® HD Voice™ technology delivers lifelike voice quality for each audio pathhandset, the hands-free speakerphone and the optional headset
- Polycom® Acoustic Clarity™ technology, providing full-duplex conversations, acoustic echo cancellation and background noise suppression
  - Type 1 compliant (IEEE 1329 full duplex)
- Frequency response: 14 kHz for handset, optional headset and hands-free speakerphone modes
- Codecs: G.711 (A-law and μ-law), G.729AB, G.722, G.722.1, G.722.1C
- Individual volume settings with visual feedback for each audio path
- · Voice activity detection
- Comfort noise generation
- DTMF tone generation (RFC 2833 and in-band)
- Low-delay audio packet transmission
- · Adaptive jitter buffers
- Packet loss concealment

## Headset and handset compatibility

- Dedicated RJ-9 headset port
- Hearing aid compatibility to ITU-T P.370 and TIA
- 504A standards
- Compliant with ADA Section 508 Subpart B 1194.23 (all)
- Hearing aid compatible handset for magnetic coupling to hearing aids
- Compatible with commercially available TTY adapter equipment
- Supports compatible USB headsets

## Call handling features<sup>1</sup>

- 12 lines (registrations)
- Up to 24 simultaneous calls
- Shared call/bridged line appearance
- Flexible line appearance (1 or more line keys can be assigned for each line extension)
- Distinctive incoming call treatment/ call waiting
- · Call timer and call waiting
- · Call transfer, hold, divert (forward), pickup
- Called, calling, connected party information
- · Local 3-way audio conferencing
- · 1-touch speed dial, redial
- · Remote missed call notification
- · Do not disturb function
- · Electronic hook switch capable
- Local configurable digit map/dial plan

## Open application platform

- WebKit-enabled full browser that supports HTML5, CSS, SSL security and JavaScript
- Supports Polycom Apps SDK and API for third-party business and personal applications
- Bundled with Polycom Productivity Suite:
  - Corporate directory access using LDAP
  - Local voice call recording on USB flash drive
  - Visual conference management

## Network and provisioning

- Network (LAN) cable CAT-5E
- · SIP protocol support
- · SDF
- IETF SIP (RFC 3261 and companion RFCs)
- Two-port gigabit Ethernet switch
  - 10/100/1000Base-TX across LAN and PC ports
  - Conforms to IEEE802.3-2005 (Clause 40) for physical media attachment
  - Conforms to IEEE802.3-2002 (Clause 28) for link
- Partner auto-negotiation
- Manual or dynamic host configuration protocol (DHCP)
- DHCP network setup
- Time and date synchronization using SNTP
- FTP/TFTP/HTTP/HTTPS server-based central provisioning for mass deployments
- Provisioning and call server redundancy supported<sup>1</sup>
- QoS support—IEEE 802.1p/Q tagging (VLAN), Layer 3 TOS, and DSCP

- VLAN—CDP, DHCP VLAN discovery, LLDP- MED for VLAN discovery
  - Network address translation support for static configuration and "Keep-Alive" SIP signaling
- RTCP and RTP support
- · Event logging
- Syslog
- Local configurable digit map/dial plan
- Hardware diagnostics
- · Status and statistics reporting
- IPv4
- TCP
- UDP
- DNS-SRV

#### Security

- 802.1X authentication and EAPOL
- Media encryption via SRTP
- · Transport layer security
- Encrypted configuration files
- · Digest authentication
- · Password login
- Support for URL syntax with password for boot server address
- · HTTPS secure provisioning
- Support for signed software executables

#### Power

- Built-in auto-sensing IEEE 802.3 at Ethernet (Class 4)
- Energy-saving smart motion detect@ower over enables the screen to go into power-save mode when no one is in the office
- External universal AC adaptor (optional, 48V 0.52A DC)

## Approvals

- FCC Part 15 (CFR 47) Class B
- ICES-003 Class B
- EN55022 Class B
- CISPR22 Class B
- VCCI Class B
- EN55024
- EN61000-3-2; EN61000-3-3
- NZ Telepermit
- Korea KC
- UAE TRA
- Russia CU
- Brazil ANATELAustralia RCM
- South Africa ICASA
- China CCC
- Saudi Arabia CITC

## Safety

- UL 60950-1
- · CE Mark
- CAN/CSA-C22.2 No. 60950-1-03
- EN 60950-1
- IEC 60950-1
- AS/NZS 60950-1

## Operating conditions

- Temperature: +32 to 104°F (0 to 40°C)
- Relative humidity: 5% to 95%, noncondensing

## Storage temperature

• -40 to +160°F (-40 to +70°C)

## Polycom® VVX® 500 Series comes with

- Polycom VVX 500 Series console
- · Handset with handset cord
- Network (LAN) cable CAT-5E
- Quick start guide

#### Size

• 7.5 x 6 x 7 in (19 x 15 x 18 cm) (W x H x D)

#### Part numbers

- 2200-44500-025 VVX 500 WW PoE
- 2200-48500-025 VVX 501 WW PoE
- 2200-44500-019 VVX 500 Skype for Business, POE
- 2200-48500-019 VVX 501 Skype for Business, POE

#### Weight

• Unit weight: 2.0 lbs (0.9 kg)

## Unit box dimensions/weight

- 11.46 x 7.9 x 3.82 in (29.1 x 20 x 9.7 cm)
- 3.1 lbs (1.4 kg)

## Master carton quantity

• 5

## Country of origin

• China

## Warranty

- 1 year
- Most software-enabled features and capabilities must be supported by the server. Please contact your IP PBXsoftswitch vendor or service provider for a list of supported features.
- To enjoy all the benefits of Polycom HD Voice when using the phone in the headset mode, you must use a wideband headset.



## **About Polycom**

Polycom helps organizations unleash the power of human collaboration. More than 400,000 companies and institutions worldwide defy distance with video, voice and content solutions from Polycom. Polycom and its global partner ecosystem provide flexible collaboration solutions for any environment that deliver the best user experience and unmatched investment protection.

Polycom, Inc. 1.800.POLYCOM www.polycom.com Polycom Asia Pacific Pte Ltd +65 6389 9200 www.polycom.com.sg Polycom EMEA +44 (0)1753 723282 www.polycom.co.uk

