



# IpChannel Bank Multi-Port FXS or FXO Gateway-Router

## SmartNode™ 4400 Series

The cost-effective Gateway-Router solution to tie in 12 to 32 analog phones, fax or PSTN trunk lines to your IP environment.

### 12, 16, 24 or 32 FXS

• Simultaneous voice or fax calls on all ports.  
Advanced local call switching.

### Full SIP and T.38 support

Supports the complete range of industry standard VoIP: SIP, H.323, T.38 fax, fax and modem bypass, DTMF relay. Codecs G.729, G.723 etc.

### Secure Toll-Quality VoIP

DownStreamQoS and Voice-over-VPN with adaptive traffic management and shaping for maximum voice quality and secure voice communication.

### Complete Access Routing

Two 10/100 Ethernet ports with auto MDI-X. Access router with NAT, Firewall, PPPoE, DHCP, DynDNS, multiple VLANs & VPN with IPsec\*

### Outstanding Interoperability

Interoperable for voice and T.38 fax with leading SIP service providers, soft-switch vendors and Asterisk™ IP-PBX

The SmartNode™ 4400 VoIP Gateway-Router provides 12 to 32 analog FXS or FXO interfaces to connect phones, fax or PSTN trunk lines to your IP-based communications (IP PBX, UC systems and SIP Trunks).

Like every SmartNode™, the SN4400 supports every industry-standard CODEC to deliver toll-quality voice on every call. The Unified Communications Agent™ (UCA) provides any-to-any multi-path switching (simultaneous SIP, H.323, ISDN, and POTS calls with routing and conversion between TDM/PSTN and IP/Ethernet networks—plus T.38 and SuperG3 FAX). VoIP-over-VPN with voice encryption provides secure voice and data via IPsec with AES/DES strong encryption and automated keying via Internet Key Exchange (IKE). In addition, advanced call-router functionality includes least-cost call routing with flexible dialed-number plan support.

The SmartNode survivability suite combines PSTN fallback, SIP Registrar and IP-link

redundancy to ensure business continuity in case the IP network fails. Patton's DownStreamQoS™ delivers the advantage of clear, uninterrupted voice-and-data communication. In addition, SmartNode delivers a smooth transition to VoIP with strong number portability support accepting incoming calls from the PSTN throughout the VoIP service provider's number porting process.

**Preserve investments** in legacy phone equipment while taking the next steps toward unified communications with the SN4400 VoIP Gateway-Router. Providing 12 to 32 FXS or FXO interfaces and two 10/100/1000 Ethernet, the SN4400 with built-in IP Router delivers secure, prioritized unified communications.

Need a carrier upgrade? The SmartNode 4900 adds a redundant power supply, WAN interfaces, cooling fans and 0–50° C operating temperature.

Visit [www.patton.com/smartnode](http://www.patton.com/smartnode) for more information.



Dual 10/100  
Ethernet ports

EIA-232  
console port

50-pin (12 to 24 channels)  
or 64-pin (32 channels)  
Telco connector

Proven  
Patton design,  
Patton supported

## Typical applications



## Specifications\*

<p><b>Capacity</b> 12, 16, 24, 32 simultaneous VoIP calls</p> <p><b>Data Services</b> Two 10/100 Ethernet ports • Complete IP access router • DHCP Client &amp; server • Packet fragmentation • Static firewall, NAT, NAPT RFC 1631 access control lists • DMZ port</p> <p><b>Quality of Service</b> Voice priority • DownStreamQoS™ • Traffic management, shaping and policing • IEEE 802.1p, TOS, DiffServ labeling • IEEE 802.1Q,</p>	<p>VLAN tag insertion/deletion (4096 VLAN IDs, multiple VLAN support)</p> <p><b>Management</b> Web/HTTP, CLI with local console and remote Telnet access • TFTP configuration &amp; firmware loading • SNMP MIB II and product MIB • Secure autoprovisioning for both firmware and unit/subscriber configuration • Built-in diagnostic tools (trace, debug, call generator)</p> <p><b>FXS Connectivity</b> 2-wire Loopstart on 50pin (12 to 24 channels) or</p>	<p>64pin (32 channels) Telco connector • Short haul loop 1.1km @3REN • EuroPOTS (ETSI EG201188) • Programmable AC impedance, feeding, ring and on-hook voltage • Caller-ID FSK and ITU V.23/Bell 202 generation</p> <p><b>FXO Connectivity</b> 2-wire Loopstart on 50pin (12 to 24 channels) or 64-pin (32 channels) Telco connector • Programmable impedance, ring detection, tone detection, disconnect supervision • Caller ID detection</p>	<p><b>Voice Signaling</b> SIPv2 H.323v4 (simultaneously with B2BUA capability) • SIP call transfer, redirect • DTMF in-band &amp; out-of-band • All tones programmable (dial, ringing, busy)</p> <p><b>Call Switching and Services</b> Regular expression based call routing and number manipulation • Number blocking • Short-dialing • Digit collection, distribution and hunt groups • transparent line extension</p>	<p><b>Voice Processing</b> CODEC G.711 a-law/mu-law, G.723, G.729ab • G.726, G.727, T.38 fax relay • G.711 transparent fax and bypass</p> <p><b>System</b> CPU Motorola MPC875 @ 133 MHz • Memory 32MB SDRAM/8MB Flash</p> <p><b>Dimensions</b> 19-in. rack-mount chassis 48.3W x 4.44H x 30.5D cm</p> <p><b>Weight</b> 4.1 kg</p>	<p><b>Power</b> 100-240 VAC (50/60 Hz) • Power dissipation: &gt; 22W (60W max, model SN4432/JS/RUI)</p> <p><b>Temperature</b> 32-104°F (0-40°C)</p> <p><b>Humidity</b> Up to 90% (non-condensing)</p> <p><b>Compliance</b> EMC compliance: EN 55022 and EN 55024 • Safety compliance: EN 50950 • CE compliance • FCC Part 15 Class A • RoHS</p>
--	---	---	--	--	---

\* Specifications subject to change without notice.

## Ordering Info

### SmartNode IpChannelBank VoIP Gateway (GW)-Router

- SN4412/JO/UI:** 12 FXO GW-Router, 2 x 10/100Base-TX, UI Power. Under Accessories, look for this symbol: ✓
- SN4412/JS/48:** 12 FXS GW-Router, 2 x 10/100Base-TX, 48V DC power. Under Accessories, look for this symbol: ✓
- SN4412/JS/UI:** 12 FXS VoIP GW-Router, 2 x 10/100Base-TX, UI Power. Under Accessories, look for this symbol: ✓
- SN4416/JO/UI:** 16 FXO VoIP GW-Router, 2 x 10/100Base-TX, UI Power. Under Accessories, look for this symbol: ✓

- SN4416/JS/48:** 16 FXS VoIP GW-Router, 2 x 10/100Base-TX, 48VDC Power. Under Accessories, look for this symbol: ✓
- SN4416/JS/UI:** 16 FXS VoIP GW-Router, 2 x 10/100Base-TX, UI power. Under Accessories, look for this symbol: ✓
- SN4424/JO/UI:** 24 FXO VoIP GW-Router, 2 x 10/100Base-TX, UI Power. Under Accessories, look for this symbol: ✓
- SN4424/JS/48:** 24 FXS VoIP GW-Router, 2 x 10/100Base-TX, 48V DC Power. Under Accessories, look for this symbol: ✓
- SN4424/JS/UI:** 24 FXS VoIP GW-Router, 2 x 10/100Base-TX, UI Power. Under Accessories, look for this symbol: ✓

- SN4432/JO/UI:** 32 FXO VoIP GW-Router, 2 x 10/100Base-TX, UI Power. Under Accessories, look for this symbol: ✓
- SN4432/JS/48:** 32 FXS VoIP GW-Router, 2 x 10/100Base-TX, 48V DC Power. Under Accessories, look for this symbol: ✓
- SN4432/JS/UI:** 32 FXS VoIP GW-Router, 2 x 10/100Base-TX, UI Power. Under Accessories, look for this symbol: ✓
- Accessories**  
Choose the color-coded symbol (✓) for your model
- 10-3096TM50/16RJ11-12:** 12 FT Cable (50 PIN TELCO-to-16 RJ11) ✓

- 10-3096TM50/16RJ45-12:** 12 FT Cable (50 PIN TELCO-to-16 RJ45) ✓
- 10-3096TM50/50-12:** 12 FT Cable (50 PIN TELCO-to-50 PIN TELCO) ✓ ✓
- 10-3096TM50-20:** 20 FT Cable (50-pin TELCO-to-25 unterminated) ✓ ✓
- 10-50TELCO/24RJ11-6:** 6 FT Cable (50 PIN TELCO-to-24 RJ11) ✓ ✓
- 10-50TELCO/24RJ45-6:** 6 FT Cable (50 PIN TELCO-to-24 RJ45) ✓ ✓
- 10-493264-10:** 10 FT Cable (64 PIN TELCO-to-32 unterminated) ✓

**PATTON**  
Let's Connect!™

**Patton Electronics Co.**  
7622 Rickenbacker Drive  
Gaithersburg, Maryland 20879  
USA  
Phone +1 301 975 1000  
Fax +1 301 869 9293  
E-mail [sales@patton.com](mailto:sales@patton.com)  
Web [www.patton.com](http://www.patton.com)

**Patton-Inalp Networks AG**  
Meriedweg 7  
CH-3172 Niederwangen  
Switzerland  
Phone +41 (31) 985 25 25  
Fax +41 (31) 985 25 26  
E-mail [sales@inalp.com](mailto:sales@inalp.com)  
Web [www.inalp.com](http://www.inalp.com)

**Patton Hungary Zrt**  
Gábor Dénes utca 4.  
Infopark Building C  
Budapest H-1117  
Hungary  
Phone +36 1 439 4840  
Fax +36 1 439 4844  
E-mail [ce@patton.com](mailto:ce@patton.com)  
Web [www.patton.com](http://www.patton.com)

07MSN4400-DS7

Patton is a registered trademark and the terms SmartNode, DownStreamQoS, and SessionRouter are trademarks of Patton Electronics Company in the United States and other countries.