## SIP Ceiling Tile Drop-In Speaker

The SIP Ceiling Tile Drop-In Speaker is a Power-over-Ethernet (PoE 802.3af/802.3at) and Voice-over-IP (VoIP) public address indoor speaker that easily connects into existing local area networks with a single CAT5/6 cable connection. The speaker is compatible with most IP PBX servers. In a non-SIP environment, the speaker is capable of playing audio from a multicast source.

CyberData has maintained one of the most comprehensive list of IP PBX servers certified to work with CyberData VoIP products.





## Features

- Autoprovisioning via HTTP, HTTPS, or TFTP
- HTTPS or HTTP web based configuration. HTTPS is enabled by default.
- 802.11q VLAN tagging
- Configurable event generation for device health and status monitoring
- Loud ringer function second SIP extension
- Paging prioritization and background music
- User upgradeable firmware via web interface or autoprovisioning
- Network-adjustable speaker volume
- Support for 10 multicast paging groups
- Support for multiple SIP servers for redundancy
- Relay for activating door locks

_		
	Specifications	
	Ethernet I/F	10/100 Mbps
	Protocol	SIP RFC 3261 Compatible
	Power Input	PoE 802.3af/802.3at compliant or 24VDC @ 1A Auxiliary Power Supply (not included)
	Audio Output	802.3af - SPL 109.2 dB @ 1 meter 802.3at - SPL 111.9 dB @ 1 meter
	On-Board Relay	1A @ 30 VDC
	Payload Types	G.711 a-law, G.711 µ-law, and G.722
	Operating Range	Temperature: -40° C to 55° C (-40° F to 131° F) Humidity: 5-95%, non-condensing
	Storage Temperature Storage Altitude	-40° C to 70° C (-40° F to 158° F) Up to 15,000 ft. (4573 m)
	Dimensions (Unit)*	Length: 12 in. [304.8 mm] Width: 3.23 in. [82.04 mm] Height: 23.75 in. [603.25 mm]
	Dimensions (Boxed)*	Length: 16.25 in. [412.75 mm] Width: 8.125 in. [206.38 mm] Height: 28.25 in. [717.55 mm]
	Weight Boxed Weight	8.2 lbs. [3.72 kg] 11.0 lbs. [4.99 kg]
	Compliance	CE; EMC Directive – Class A EN 55032 & EN 55024, LV Safety Directive – EN 60950-1, RoHS Compliant, FCC; Part 15 Class A, Industry Canada; ICES-3 Class A, IEEE 802.3 Compliant
	Warranty	2 Years Limited
	Part Number	011401
	*Dimensions are measured f	from the perspective of the product

\*Dimensions are measured from the perspective of the product being upright with the front of the product facing you.

**Related Products:** 




011201 Ceiling Tile Auxiliary Analog Drop-In Speaker



011288 Auxiliary RGB Strobe Kit



011146 SIP Paging Server with Bell Scheduler SIP Ceiling Tile Drop-In Speaker



SIP Ceiling Tile Speaker with Extra Speaker Connection

