InformaCast Enabled Wall Mount Speaker



The CyberData InformaCast Enabled Wall Mount Speaker is an economical Power-over-Ethernet (PoE 802.3af) and Voice-over-IP (VoIP) public address product that plays InformaCast and multicast messages. It easily connects to your PoE network with a single Ethernet cable connection. The device's streamlined case and mounting hardware offers an easy installation in almost any environment.

Features

- Capable of receiving Singlewire InformaCast and multicast messages
- Supports Singlewire InformaCast High Quality Audio
- Supports audio prioritization for 10 multicast paging groups
- Can receive pages directly from Poly phones as well as other devices that can send standard multicast
- Network-adjustable speaker volume
- High efficiency speaker driver
- Small footprint
- TLS security for autoprovisioning and web-based configuration
- 802.11q VLAN tagging
- Configurable event generation for device health and status monitoring
- User upgradeable firmware via web interface or autoprovisioning

Related Products:



011504 InformaCast Enabled Ceiling Speaker



011446 Multicast VoIP Microphone



	Specifications	
	Ethernet I/F	10/100 Mbps
	Protocol	RTP
	Notification Software	Singlewire InformaCast v4.0 and above
	Power Input	PoE 802.3af
	Audio Output	802.3af - SPL 98 dB @ 1 meter
	Payload Types	G.711 a-law, G.711 μ -law, and G.729
	Network Security	TLS/SSL 1.2
	Operating Range	Temperature: -40 $^{\circ}$ C to 55 $^{\circ}$ C (-40 $^{\circ}$ F to 131 $^{\circ}$ F) Humidity: 5-95%, non-condensing
	Storage Temperature Storage Altitude	-40° C to 70° C (-40° F to 158° F) Up to 15,000 ft. (4573 m)
	Dimensions*	6.42 in. [163 mm] Length 5.39 in. [137 mm] Width 9.18 in. [233 mm] Height
	Weight Boxed Weight	3.8 lbs [1.72 kg] 4.4 lbs [1.96 kg]
	Compliance	CE; EMC Directive – Class A EN 55032 & EN 55024, LV Safety Directive – EN 60950-1, RoHS Compliant, FCC; Part 15 Class A, Industry Canada; ICES-3 Class A, IEEE 802.3 Compliant
	Warranty	2 Years Limited
	Part Number	011505


*Dimensions are measured from the perspective of the product being upright with the front of the product facing you.



011146 SIP Paging Server with Bell Scheduler

InformaCast Enabled Wall Mount Speaker

Typical IP Speaker Configuration



Dimensions

