

BTN-KIT-MIC-ND Call Button Kit with Microphone



OVERVIEW

The Call Button Kit with Microphone (BTN-KIT-MIC-ND) easily connects via RJ25 cable to IP compatible devices and enables two-way communication.

AUDIO FUNCTIONALITY



Intercom, page, or all-call Trigger pre-programmed text, or privacy mode

SIP INTEGRATION



Enable SIP calls Dial out pre-programmed internal extensions and external phone numbers

SOLUTIONS

- Paging
- Intercom
- Emergency notification

MICROPHONE



Hands-free talk back Monitoring

SOFTWARE



Diagnostic software included Compatible with third-party software, including InformaCast, Revolution, and Cisco CallManager

ADDITIONAL FEATURES

- Built-in web server
- Requires RJ25 cable (6P6C)

MOUNTING

 Standard junction box required for mounting

BUTTON LED



Illuminates when microphone is active

NOTIFICATION



Trigger alerts that activate other devices, such as a strobe or electronic lock

DUAL COMMANDS



Program button push and release / push and hold modes Accommodates up to two extensions or phone numbers

COMPATIBLE IP DEVICES

Round Ceiling IP Speaker IPSCM-RMe

Square Ceiling Tile IP Speaker IPSCM

IP Speaker Flush/Surface Mount IPSWS-SM, IPSWS-FM

> HD IP Display IPCSHD

Compatible with MAC address 0a:xx:xx and above

SOFTWARE

The BTN-KIT-MIC-ND integrates easily with third-party mass notification software, as well as SIP and VoIP phone systems, enabling a facility to take advantage of all the device capabilities. The device also comes with diagnostic software (compatible to run alongside third-party software), and an on-board web server interface, both which provide the ability to monitor and troubleshoot the ANetD devices on the network.

Third-Party Software

- InformaCast (Singlewire)
- Revolution (Syn-Apps)
- IPSession (IPCelerate)
- MessageNet Systems
- BellComander (Acro Vista)
- And more!

VoIP Phone Systems

- Cisco CallManager
- Mitel
- Avaya
- 3CX Polycom
- And more!

IPClockWise

- Diagnostic tool included with device purchase
- Complements investment in third-party software
- Developed and supported by Advanced Network Devices

DIMENSIONS





SPECIFICATIONS	BTN-KIT-MIC-ND
FACEPLATE MATERIAL	16-gauge brushed stainless steel
ELECTRICAL LIFE	200,000 cycles
POWER CONNECTION	RJ25 cable (6P6C)
SWITCH FUNCTION	Momentary ON
OPERATING TEMPERATURE	-20° to 50° C (-4° - 131° F)
CIRCUIT	SPST
INSTALLATION DEPTH	1" (25.4 mm)
DIMENSIONS	2.75" W x 4.5" H
WEIGHT	TBD
WARRANTY	2 Year Limited

Due to continual product development, specifications are subject to change without notice.



