



NetVanta

Adtran
Data Sheet

1570-24-370W

Layer 3, PoE+ Gigabit Ethernet Switch



Gigabit



Power over
Ethernet



VoIP



Low TCO

Benefits

- 24 - 10/100/1000 Base-T Ethernet ports
- Up to four SFP+ ports with support for 10 Gbps
- RJ-45 console port and micro-USB port for management
- Non-blocking Layer 2 and Layer 3 Lite switching capacity up to 128 Gbps
- Fully managed (Web GUI, CLI, SNMP)
- Industry standard CLI and config
- 802.3at (POE+), 802.3af (PoE) and Legacy PoE support up to 370W
- Feature-rich Adtran switch engine for enterprise Ethernet switching
- Supports 802.1q VLANs and trunking, STP, IGMP
- Advanced smart switching features (ACLs, L2/L3/L4 DiffServ, QoS policies, LACP link aggregation, broadcast control, denial of service protection)
- Faster VoIP deployments with VoIP VLAN and discovery
- Port queue-level policing and shaping

Overview

The **NetVanta 1570-24-370W** is an enterprise-class, fully managed Gigabit PoE+ switch. This switch is perfect for supporting highly resilient IoT, cloud applications, and Voice over IP (VoIP). It is purpose built for enterprises looking to upgrade their networks with high-performance, reliable, scalable and easy-to-manage switching solutions. NetVanta 1570-24-370W switch offers advanced multilayer switching, high-bandwidth capabilities, voice-aware features, and the right functionality to enable scaling from small business to enterprise-sized networks.

Best VoIP Switch, Period.

The NetVanta 1570-24-370W is the best switch for VoIP, delivering high voice fidelity, faster VoIP deployment, ease of management, and maximum network uptime.

- **Voice Fidelity:** The switch provides 24 GigE ports with four 10 Gbps SFP+ ports, delivering up to 40 Gbps of uplink capacity to support a greater number of HD voice connections, video streaming, Wi-Fi® and other bandwidth-intensive applications.
- **Faster Deployment and Ease of Use:** Custom VLAN Organization Unique Identifier (OUI) assignment simplifies VoIP deployments. The switches offer flexible management options including Web GUI and Command Line Interface (CLI).
- **Maximum Uptime:** NetVanta 1570-24-370W includes an industry-standard warranty, world-class product support, advanced hardware replacement, and optional ProCare Service minimizing business risk.

Security

NetVanta 1570-24-370W offers a variety of data security features including Denial of Service (DoS) protection, MAC-based port security, 802.1x port authentication, multilevel user passwords, Secure Shell (SSH), ARP Inspection and Secure Socket Layer (SSL) for encrypted user login. Additionally, these switches support Authentication, Authorization and Accounting (AAA) for authentication with RADIUS and TACACS+.

Redundancy and Convergence

These switches support common Ethernet protocols like Spanning Tree, Rapid Spanning- Tree, Multiple Spanning Tree

Administration

The Adtran switch engine offers both a CLI and an intuitive Web-based GUI. To automate setup and configuration, NetVanta 1570-24-370W enables DHCP out of the box that provides the ability to discover and provision the switch configuration. Tools such as network forensics, cable, and SFP diagnostics simplify troubleshooting.

NetVanta 1570-24-370W can also be remotely managed by the Adtran n-Command® MSP platform. Adtran n-Command offers the ability to discover devices, make mass configuration changes or firmware upgrades, backup/restore configurations, and generate inventory reports for asset management. Adtran n-Command MSP also offers VoIP VQM and reporting, as well as an industry-leading, easy-to-use, GUI.

NetVanta 1570-24-370W

Product Specifications

Physical Interfaces

Ethernet Ports

- 24 x 10/100/1000Base-T
- 4 x Multi-rate SFP+ Ports (1G/10G)

Console Port

- RJ-45
- Micro USB

Switching Performance

- Non-blocking Layer 2/3 Lite Switching
- 32,000 MAC addresses
- 4,000 VLANs
- Switching Performance: 128Gbps
- Forwarding Performance: 95.232 Mpps

Layer 2 Support

- 802.1d Spanning Tree
- 802.1w Rapid Spanning Tree
- 802.1s Multiple Spanning Tree
- 802.1q VLAN switching and Trunking
- 802.3ad Link Aggregation
- Jumbo Frames (12288)
- Static and Dynamic LACP trunks (IEEE 802.3ad)
- IGMP v1/v2/v3 Snooping/Querier/Proxy
- MLD v1/v2 Snooping
- 802.3x Flow Control
- GVRP/MRP/MVRP
- Loop Protection Layer 3 Support

Layer 3 Lite Support

- DHCP Server & Relay
- 2000 ARP Entries
- IPv4/IPv6 L3 Static Routes
- OSPF v2/v3
- RIP v1/v2
- Route Table
 - IPv4 Routes 18K
 - IPv6 routes 9K

Diagnostics

- Port and Flow Mirroring
- Uni Directional Link Protection
- LLDP (802.1ab)
- LLDP-MED
- Ping, Traceroute
- sFlow
- Cable Diagnostics

Front Panel Status LEDs

- System
- LAN: Link, Activity
- LED Port Button: Toggle Port LEDs between Link, Activity, and POE Status

Quality of Service

- 802.1p, Drop Precedence Level, DSCP, Priority
- Eight Hardware Queues per Port
- Classification and Remarking ACLs
- Strict Priority Scheduling
- Weighted Round Robin (WRR)
- Policing and Shaping Per Port
- 802.1x Port- and Queue-based
- WRED
- QoS Control List
- Drop Eligible Indicator
- Ingress and Egress Maps
- Storm Policing

VLAN

- 4K VLANs Simultaneously
- Port-based VLANs
- 802.1Q Tagged Trunked
- Port-based VLAN
- Private VLANs
- Voice VLANs
- Guest VLANs
- 802.1v Protocol VLAN
- MAC-based VLAN
- IP Subnet-Based VLAN
- Management VLAN
- Q-in-Q VLAN
- GARP VLAN Registration Protocol (GVRP)

Layer 3 Lite Gigabit Ethernet Switches with PoE+

Security

- 802.1x Port Authentication
- L2 VLAN Client Isolation
- Port Security
- IP Source Guard
- RADIUS/TACACS+
- DoS Protection
- DHCP Snooping
- Hardware ACLs
- Users and Privilege Levels
- ARP Inspection

Administration

- CLI (Console/Telnet/ SSH)
- SNMP v1, v2c, v3
- Web-based GUI
- Dual image
- SYSLOG
- RMON
- sFlow
- RADIUS
- TACACS+
- NTP
- n-Command Support

PoE

- 802.3af (PoE), 802.3at (PoE+) and Legacy PoE
- Max 30 Watts per Port
- Total 370W Available Power
- 802.3az Energy Efficient Ethernet
- Power Management
- PoE Scheduling

Environment

- Operating Temperature: 32° to 122°F (0° to 50°C)
- Storage Temperature: -40° to 158°F (-20° to 70°C)
- Relative Humidity: Up to 90%, Non-condensing

Physical and Power

- NetVanta 1570-24-370W
 - Chassis: 1U Metal Enclosure
 - Mount: Desktop, Wall, and Rack
 - Dimensions: 1.73 in. x 17.4 in. x 8.3in. (4.4 cm x 44.2 cm x 21.1 cm) (H x W x D)
 - Weight: 8.4 lbs (3.8 Kg)
 - Voltage: 100-240 VAC, 50/60 Hz
 - Max Wattage with PoE: 475W

Agency Approvals

- CB (IEC 62368-1)
- UL (UL 62368-1)
- FCC
- CE/EMC
- EN 300 386

Warranty

- Limited Lifetime Warranty



NetVanta 1570-24-370W Front

NetVanta 1570-24-370W

Ordering Information

Equipment	Part No.
Chassis	
NetVanta 1570-24-370W	17101574PF1
SFPs	
1000Base-SX 850nm SFP	1200480E1
1000Base-LX 1310nm SFP	1200481E1
1000BaseT Copper SFP	1200485G1
2.5 Gbps Multimode SFP	1200482G1
2.5 Gbps Singlemode SFP	1200483G1
10G Base-SR 850nm SFP+	1700485F1
10G Base-LR 1310nm SFP+	1700486F1
25GBase-SR SFP28	1700487F1
25GBase-LR SFP28	1700488F1
Interconnect Cables	
SFP28 (1 meter)	1700489F1
SFP+ (1 meter)	1710484F1
SFP+ (3 meter)	1710484F3
SFP+ (5 meter)	1710484F5
Brackets	
19" Rackmount Bracket - 24/48 Port	1700519F1
Wallmount Bracket - 24 Port	1700520F1



Adtran Corporate Headquarters
901 Explorer Boulevard
Huntsville, AL 35806
USA
adtran.com
sales@adtran.com

Adtran Europe Limited
Building 2200 Basing View
Basingstoke RG-21 4EQ, UK
contact@adtran.com

Adtran GmbH
Jean-Monnet-Straße 4,
10557 Berlin, Germany
kontakt@adtran.com

Adtran Networks Pty. Limited
L5 330 Collins Street
Melbourne, Victoria, 3000
Australia
australia@adtran.com

617101574PF1-8A

October Copyright © 2022 Adtran, Inc. All rights reserved. Adtran believes the information in this publication to be accurate as of publication date, and is not responsible for error. Specifications subject to change without notice. Adtran and the other trademarks listed at www.adtran.com/trademarks are registered trademarks of Adtran, Inc. or its affiliates in various countries. All other trademarks mentioned in this document are the property of their respective owners.

Adtran warranty duration and entitlements vary by product and geography. For specific warranty information, visit www.adtran.com/warranty

Adtran products may be subject to U.S. export controls and other trade restrictions. Any export, re-export, or transfer of the products contrary to law is prohibited. For more information regarding exportation of Adtran items (e.g. commodities, technology, software), please visit www.adtran.com/export license.



ISO 9001
ISO 14001
TL 9000