# Analog Wall Mount Speaker 25V/70V/8 Ohm

When paired with the new CyberData SIP Paging 25V/70V Amplifier, the Analog Wall Mount 25V/70V/8 Ohm Speakers offer a cost-effective solution that can greatly extend the sound coverage area.

The Speaker offers the option of constant voltage at either 25 or 70 volts as well as a traditional 8 Ohm setting. Each Speaker is configured with 5 power tap settings.

Easy to install, multiple Speakers can tee off a single home run cable to the SIP Paging 25V/70V Amplifier.

### Features

- Supports 25V, 70V or traditional 8 Ohm power input
- Multiple power tap settings for desired dB output
- Designed for good speech intelligibility
- Suitable for background music
- High efficiency speaker driver
- Easy installation

#### Modes 8 Ohm, 25V, 70V **Direct Impedance** 8 Ohms Power Handling 20 watts continuous duty Power Input 25V, 70V or 8 Ohm Audio Output\* Power Taps 1.25W 3.75W 10W 30W 25V 85.4 90 93.6 97.8 70V 85.9 90.5 94.4 98.8 Frequency Response 60 to 20000 Hz **IP** Rating IP64 Storage Temperature -40° C to 70° C (-40° F to 158° F) Storage Altitude Up to 15,000 ft. (4573 m) Temperature: -40° C to 55° C (-40° F to 131° F) **Operating Range** Humidity: 5-95%, non-condensing Dimensions\*\* 7.224 inches [183.5 mm] Length 7.453 inches [189.3 mm] Width (with bracket) 9.960 inches [253 mm] Height **Boxed Weight** 5.2 lbs [2.36 kg] Weight 6.7 lbs [3.04 kg]

\* dBc output measured @ 1M and 1 kHz

Warranty

Part Number

\*\*Dimensions are measured from the perspective of the product being upright with the front of the product facing you.

011590

2 Years Limited





011579 SIP Paging 25V/70V Amplifier



Specifications



# Analog Wall Mount Speaker 25V/70V/8 Ohm

## Typical Analog Installation



## Analog Wall Mount Speaker db Output Levels\*

	Power Tap Settings			
Voltage	1.25W	3.75W	10W	30W
25V	85.4	90	93.6	97.8
70V	85.9	90.5	94.4	98.8

\* dBC @ 1M and 1kHz



## Speaker Matrix Example

Note: Configuration as pictured above					
	Qty	Power Tap	Total		
Ceiling Speakers	6	3.75W	22.5W		
Wallmount	4	10W	40W		
Horns	3	15W	_45W		
			107.5W		

# Analog Wall Mount Speaker 25V/70V/8 Ohm

