

SIP Hand Wave Indoor Intercom

CyberData

The IP Endpoint Company

The SIP Hand Wave Indoor Intercom is a **gesture-activated** device delivering **touch-free** two-way communication and secure access control for your VoIP phone system.

Activated by a hand wave, this device is ideal for high-traffic settings such as medical facilities, commercial/residential facilities, schools and universities, retail establishments, warehouses, and manufacturing plants.

CyberData's SIP-enabled VoIP products are compatible with a vast majority of VoIP systems including SBCs, Gateways, and phone systems both on-premise or cloud-based.

Features

- Full duplex audio with enhanced acoustic echo cancelling
- Simultaneous SIP and multicast
- Supports user-uploadable ring and alert tones
- Loud/Night Ringer function - second SIP extension
- Can receive pages directly from Poly phones as well as other devices that send standard multicast
- **Touchless activation** reduces spread of infectious diseases
- Distance for hand wave activation can be set for 2,4, or 6 inches
- DTMF-controlled dry relay contact for auxiliary control
- Door closure and tamper alert signal
- Network volume control
- Supports Auxiliary Strobe Kit for visual notification
- Easy-to-clean stainless steel faceplate
- Flush mounting offers a clean streamlined installation
- TLS 1.2 and SRTP enhanced security for IP endpoints in a local or cloud-based environment
- Autoprovisioning via HTTP, HTTPS, or TFTP
- HTTPS or HTTP web based configuration. HTTPS is enabled by default.
- Configurable event generation for device health and status monitoring
- 802.11q VLAN tagging
- Web-based upgradeable firmware
- Support for Cisco SRST resiliency





Specifications


Ethernet I/F	10/100 Mbps
Protocol	SIP RFC 3261 Compatible
Power Input	PoE 802.3af compliant or +8 to +12VDC @ 1000mA Regulated Power Supply (not included)
Speaker Output	802.3af - SPL 85dB @ 1 meter
On-Board Relay	1A @ 30 VDC
Payload Types	G.711 a-law, G.711μ-law, G.722, and G.729
Network Security	TLS 1.2, SRTP, HTTPS
Operating Range	Temperature: -40° C to 55° C (-40° F to 131° F) Humidity: 5-95%, non-condensing
Storage Temperature	Temperature: -40° C to 70° C (-40° F to 158° F)
Storage Altitude	Up to 15,000 ft. (4573 m)
Dimensions*	5.827 inches [148 mm] Length 2.319 inches [59 mm] Width 7.205 inches [183 mm] Height
Weight	1.0 lbs. [0.45 kg]
Boxed Weight	2.2 lbs. [1.0 kg]
Compliance	CE: EMC Directive – Class A EN 55032 & EN 55024, LV Safety Directive EN 62368-1; RoHS Compliant; FCC Part 15 Class A; Industry Canada ICES-3 Class A; IEEE 802.3 Compliant; TAA Compliant
Warranty	2 Years Limited
Part Number	011530

*Dimensions are measured from the perspective of the product being upright with the front of the product facing you.

SIP Hand Wave Indoor Intercom



SIP Hand Wave Indoor Intercom



Related Products:



011375 Network Dual Door Strike Relay



011269 Door Strike Intermediate Relay Module



011288 Auxiliary RGB (Multi-Color) Strobe Kit



011490 Outdoor Auxiliary RGB (Multi-Color) Strobe Kit