



W626W Ruggedized Wi-Fi Phone

Datasheet

The ruggedized Wi-Fi phone W626W is designed for reliable wireless communication in enterprise and industrial environments, including offices, warehouses, healthcare and more. With an IP67 protection level, 1.8-meter drop resistance, and antibacterial and chemical-resistant materials, it delivers enhanced durability and hygiene protection for daily use in demanding scenarios.

Supporting up to 8 SIP accounts and 6-party audio conferencing, the device provides greater flexibility for multi-line communication and team collaboration. The 2.4-inch color display ensures a clear and intuitive user experience.

Equipped with dual-band 2.4G/5G Wi-Fi 6 and Bluetooth 5.0, the handset enables stable connectivity and seamless roaming across wireless networks. HD audio with intelligent noise reduction ensures clear voice communication, even in noisy environments.

In addition, the device supports H.264 video decoding, extending communication from voice to visual interaction. A dedicated emergency key enables fast alert triggering. With WPA3 and TLS 1.3 security, the device enhances data protection.



Highlights

- 2.4-inch color display with support for H.264 video decoding
- IP67-rated for water and dust resistance; withstands drops up to 1.8 meters, ensuring robust durability
- 3100mAh high-capacity battery for long-lasting battery life
- Up to 13 hours talk time and 240 hours standby time (Laboratory data)
- HD audio with intelligent noise reduction and acoustic shield technology
- Dedicated red emergency alarm key for instant emergency calls and automatic alert triggering;
- Built with antibacterial materials, suitable for factory and hospital settings.
- Supports Wi-Fi 6 and Bluetooth 5.0 connectivity
- WPA3 and TLS 1.3 support for enhanced communication security
- Support desktop and wall-mounted installation

Note: Supports up to 4CIF video resolution; data from Fanvil Lab.



HD Audio



IP67



Long
Battery Life



Alarm Call



Chemical
Cleaning
Resistant



TLS1.3
Supported



Video
Decoding

Specifications

Media

Hands free loudspeaker	2 W speaker
Microphones	2 x Mic
Audio	Intelligent noise cancellation
	Acoustic shield
	Acoustic Echo Cancellation (AEC)
	Automatic Gain Control (AGC)
	Voice Activity Detection (VAD) / Comfort Noise Generation (CNG) / Background Noise Estimation (BNE)
	Packet Loss Concealment
	RTCP-XR (RFC3611), VQ-RTCPXR (RFC6035)
	DTMF
Narrowband Codec	In-band, Out-of-Band – DTMF-Relay(RFC2833) / SIP INFO
Wideband Codec	G.711A/U, G.726, G.723.1, G.729, G.729A, G.729B, G.729AB, iLBC
Video Decoding	G.722, Opus
Video Resolution	H.264
	SQCIF, QCIF, QVGA, CIF, VGA ,4CIF

User interfaces

Screen	2.4" 240 x 320 TFT color screen
	Screen saver
	Personalized background image
	Screen backlight adjustment
	Self-adaptive acceleration-sensing screen off during calls
Keyboard	12 standard phone digit keys
	4 navigation keys and 1 OK key
	6 function keys: dial, hang-up, hands-free, phone book, mute, call transfer
	2 volume control keys (Up/Down)
	3 soft keys
	1 Push-to-Talk (PTT) key
	1 alarm key
	White backlit keyboard
Status indicator light	Orange, Green, Red

Phone Features

Generic	8 SIP lines
	Vibration Function
	Network time synchronization
	Personalized ringtone settings
	Volume adjustment
	Memorandum

	Voicemail (MWI)
Alarm	Button/ Man Down/ No Movement/ Running
	Auto-Answering
	Call out / Answer / Reject
	Call waiting / Switch
	Call forwarding
	Speed Dial
	Intercom
Call Features	Anonymous Call (Hide Caller ID / Ban Anonymous call)
	6-way Audio Conference
	Direct IP call without SIP proxy
	Emergency Call
	Caller ID Display
	Do-Not-Disturb(DND) / Timed DND
	PTT One-touch call
	1000 Local contacts
Phone book	Remote phone book (XML/LDAP, 1000 entries)
	Restricted Incoming Numbers, Allowed Incoming Numbers, Restricted Outgoing Numbers
Multi-language optional	English/ Chinese/ Traditional Chinese / Russian/ Italian/ German/ Japanese/ French/ Hebrew/ Spanish/ Catalan/ Basque/ Galician/ Turkish/ Slovenian/ Czech/ Dutch/ Korean/ Ukrainian/ Portuguese/Arabic/ Thai
Call logs	600 call logs
Maintenance	
Auto-Provisioning	FTP / TFTP / HTTP / HTTPS / DHCP Option 66/ SIP PnP
Management Protocol	TR-069, FDMCS
Firmware upgrade	OTG / Web-based upgrade
	Web-based packet-dump
Troubleshooting	Configuration export / import
	Syslog
Network	
	Dual-band Wi-Fi 6 (802.11 a/b/g/n/ac/ax)
Wi-Fi	2.4 GHz IEEE 802.11 b/g/n/ax
	5 GHz IEEE 802.11a/n/ac/ax
	802.11 k/v/r seamless roaming
Quick network connect	Batch connect network by sharing Wi-Fi networks
	Connect network by scanning the QR code with mobile phone.
Bluetooth	BT 5.0

	Protocols	Bluetooth headsets: Answer/end/mute/redial/volume adjustment
		IPv4/IPv6/IPv4&IPv6
		DNS-SRV
		STUN
		DHCP
		SNTP
Security	Voice encryption	SRTP
	Transmission encryption	TLS 1.2, TLS 1.3
	Wireless encryption	WPA / WPA2-PSK / WPA3, 802. 1X EAP
	Others	Configuration encryption
		Keypad lock
		Menu encryption
Interface	Type-C	USB 2.0
	Headset jack	Type-C
	Charging Port	Type-C, 2 x Contact pins
Power	Charging Methods	Charging base and Type-C charging
	DC input	5 V/2 A
	Battery Capacity	3100 mAh
	Battery life	Up to 13 hours talk time (Laboratory data)
		Up to 240 hours standby time (Laboratory data)
Environmental Factors	Operating humidity	5 ~ 95% (non-condensing)
	Operating temperature	-10℃ ~ 45℃
	Storage temperature	-20℃ ~ 60℃
Physical Features	Safe Drop height	1.8 m
	Protection Rating	IP67
	Material	Antibacterial design, chemical cleaning resistant
	Product Weight	TBD (g)
	Product Dimensions	161 x 55 x 24.5 mm
Package Features	Gift-Box Dimensions	195 x 188 x 75 mm
	Dimensions carton	400 x 398 x 410 mm (20 pcs)
	Carton Net weight	11.32 (kg)
	Carton Gross weight	12.24 (kg)
	Package Contents	W626W portable WiFi phone
		5 V/2 A adapter

	Charging base
	Belt clip
	Rechargeable battery
	Quick installation guide
Compliance	CE FCC RoHS

About LINKVIL

As a sub-brand of Fanvil, LINKVIL focuses on the research and development of A&V-IoT wireless communication products. Based on Audio & Video -IoT, LINKVIL helps customers to achieve full connection of wireless communication systems and will build a wireless communication Eco-system for multi-scenarios to help different industries accelerate their digital transformation.

Copyright

Copyright © 2025 Fanvil Link Technology Co., Ltd.

All rights reserved. No parts of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, photocopying, recording, or otherwise, for any purpose, without the express written permission of Fanvil Link Technology Co., Ltd.

More Information

The above specifications may be updated in the future without prior notice. All hardware/software/physical features should be based on the final shipped products.

For more information, please visit: www.fanvil.com

Fanvil | **LINKVIL**

Fanvil Link Technology Co., Ltd.

Web: www.fanvil.com

Tel: +86-755-2640-2199

E-mail: sales@fanvil.com

Add: 13th Floor, Building 2, Runzhi R&D Center, Xin'an Street, Bao'an District, Shenzhen, China